

指針絕緣阻抗計

ANALOG INSULATION TESTER



1125 IN



1126 IN

- 高品質高感度吊線式防震表頭
- 量測功能包含絕緣(高阻)和交流電壓(ACV)
- 量測絕緣阻抗時，有LED燈號顯示
- 可檢視電池電力不足設計
- 交流電壓量測可直接量測，不必按測試鍵
- 通過歐洲安全規範檢驗IEC/EN 61010-1 CAT III 600V

電氣規格(23±5°C ≤ 85%RH)

絕緣阻抗(MΩ)

1125 IN

1126 IN

量測電壓(DCV)	500V	1000V
量測電壓最大容許	額定值+10%	
量測範圍	0~1000MΩ	0~2000MΩ
容許誤差	1~500MΩ : ±5%讀值	2~1000MΩ : ±5%讀值
	其他範圍 : ±0.7%刻度長	
短路電流	1mA	

交流電壓(ACV)

量測範圍	0~600V
容許誤差	±2.5%滿刻度

一般敘述

操作溫濕度	0°~40°C 最大相對濕度 85%
儲存溫濕度	0°~50°C 最大相對濕度 75%
使用電源	1.5V(三號電池. SUM-3) x 8(顆)
外形尺寸	175(長) x 85(寬) x 75(高)mm
重量	約 560 克(含電池)
附件	測試線一組(AL-24) 說明書 x1(本) 肩帶 x1(條) 電池 x8(顆)

ANALOG INSULATION TESTER



1125 IN



1126 IN

FEATURES

- High quality Taut Band movement.
- It is a light and portable combination instrument For testing insulation(MΩ) and AC voltage.
- LED indication works when testing insulation.
- Use a high efficiency and accurate DC-DC converter.
- Battery check facility.
- AC voltage measurement can be made without depressing the test button.
- IEC/EN 61010-1 CAT III 600V

	1125 IN	1126 IN
Insulation Resistance		
Test Voltage(DC V)	500V	1000V
Output Voltage on Open Circuit	Rated test voltage +10%	
Measuring Ranges (Mid-scale value)	0-1000MΩ(20MΩ)	0-2000MΩ(50MΩ)
Accuracy	1-500MΩ : ±5% rdg	2-1000MΩ : ±5% rdg
	0.7% of scale length at other ranges	
Short Circuit Current	1mA	
AC Voltage		
Range	0-600V	
Accuracy	±2.5% of full scale	
General		
Operating Temperature & Humidity	0°-40°C relative humidity up to 85%	
Storage Temperature & Humidity	-0°-50°C relative humidity up to 75%	
Power Source	1.5V(SUM-3. R6. AA) x 8	
Dimensions	175(L) x 85(W) x 75(H)mm	
Weight	Approx. 560 g(Batteries included)	
Accessories	Test leads (Model : AL-24)	
	Instruction manual	Shoulder belt
	Batteries	Pouch