



# STANDARD

# 座式用表



CE

## ED-205

- 供學校電學教學和訓練用
- 供農場電力設備比對和維護用
- 外形尺寸：91(長)×103(寬)×100(高)公厘
- 刻度長：65 公厘
- 指示角度：90°
- 多功能式或隱藏式的極插座
- 材質：  
壓克力蓋，外殼塑膠，刻度板白底黑字
- 安規條款：  
IEC/EN 61010-1 CAT III 600V  
EN 61326-1 EN 61000-4-2 EN 61000-4-3

名稱	規格		編號
交流電流表 (AC Ammeter)	1 檔	1A	205ACA 100
		500mA	205ACA 101
		5A	205ACA 102
	2 檔	1/10A	205ACA 200
		10/100mA	205ACA 201
		100/500mA	205ACA 202
		500mA/1A	205ACA 203
		80/200mA	205ACA 204
		50mA/500mA/5A	205ACA 301
	3 檔	500mA/1A/5A	205ACA 302
		1/2.5/5A	205ACA 303
		5/10/25A	205ACA 304
交流電壓表 (AC Voltmeter)	1 檔	30/100/500mA	205ACA 305
		5V	205ACV 100
		10V	205ACV 101
		20V	205ACV 102
		50V	205ACV 103
	2 檔	250V	205ACV 104
		10/100V	205ACV 201
		3/30V	205ACV 202
	3 檔	5/15V	205ACV 203
		15/30/50V	205ACV 301
直流電流表 (DC Ammeter)	1 檔	30/50/100V	205ACV 302
		50uA	205DCA 100
		100uA	205DCA 101
		500uA	205DCA 102
		3mA	205DCA 103
		10mA	205DCA 104
		100mA	205DCA 105
		200mA	205DCA 106
		300mA	205DCA 107
		500mA	205DCA 108
		500uA	205DCA 109
		1A	205DCA 110
		2.5A	205DCA 111
		3A	205DCA 112
	5A	205DCA 113	
	10A	205DCA 114	
	2 檔	1/10mA	205DCA 200
		1/5A	205DCA 201
		1/10A	205DCA 202
		5/500mA	205DCA 203
	3 檔	50mA/500mA/5A	205DCA 301
100mA/1A/5A		205DCA 302	
1/5/10A		205DCA 303	

名稱	規格		編號	
直流電壓表 (DC Voltmeter)	1 檔	1mV	205DCV 100	
		1V	205DCV 101	
		3V	205DCV 102	
		5V	205DCV 103	
		6V	205DCV 104	
		10V	205DCV 105	
		15V	205DCV 106	
		20V	205DCV 107	
		2 檔	50/500mV	205DCV 200
			50/500uA	205DCV 201
	1/10V		205DCV 202	
	1/5V		205DCV 203	
	2/20V		205DCV 204	
	3/15V		205DCV 205	
	5/10V		205DCV 206	
	5/15V		205DCV 207	
	10/50V		205DCV 208	
	30/60V		205DCV 209	
	3 檔		50/500/5000uA	205DCV 301
		100uA/500uA/1mA	205DCV 302	
		3/10/15V	205DCV 303	
3/15/30V		205DCV 305		
3/30/300V		205DCV 306		
檢流計 (Galvanometer)		+/- 0.1mA	205G 100	
		+/- 0.5mA	205G 101	
		+/- 10V	205G 102	
		+/- 1A	205G 103	
		+/- 3.5G	205G 104	
		+/- 3.5mA	205G 105	
		+/- 30G	205G 106	
		+/- 30mA	205G 107	
		+/- 35G	205G 109	
		+/- 35mV	205G 110	
		+/- 50G	205G 111	
		+/- 60uA	205G 112	
特殊規格 (Custom)		+1A-0-5A	205DC 101	
		+20uA-0-100uA	205DC 102	
		+20mA-0-100mA	205DC 103	
		+5V-0+5V	205DC 104	
		+50mA/500mA/5A	205DC 105	
		+3/15/300V	205DC 106	

※特殊規格可以另行設計訂製

<http://www.51082245.com/sew.htm>



# STANDARD

# BENCH TYPE



## ED-205

- **Dimension :**  
91(L)×103(W)×100(D)mm
- **Scale Length :**  
Approx. 65mm (deflection angle : 90°)
- **Terminal :**  
4mm socket captive head, suitable for wire or pin-type test lead.
- **Material And Color :**  
Acrylic resin meter cover, white scale plate, plastic stand in black.
- **Safety Standard :**  
IEC/EN 61010-1 CAT III 600V  
EN 61326-1 EN 61000-4-2 EN 61000-4-3

Name	Range	No.	
AC Ammeter (Rectifier Type) Accuracy : ±2.5% F.S.	1 Range	1A	205ACA 100
		500mA	205ACA 101
		5A	205ACA 102
	2 Ranges	1/10A	205ACA 200
		10/100mA	205ACA 201
		100/500mA	205ACA 202
		500mA/1A	205ACA 203
		80/200mA	205ACA 204
		50mA/500mA/5A	205ACA 301
	3 Ranges	500mA/1A/5A	205ACA 302
		1/2.5/5A	205ACA 303
		5/10/25A	205ACA 304
		30/100/500mA	205ACA 305
5V		205ACV 100	
1 Range	10V	205ACV 101	
	20V	205ACV 102	
	50V	205ACV 103	
	250V	205ACV 104	
	10/100V	205ACV 201	
2 Ranges	3/30V	205ACV 202	
	5/15V	205ACV 203	
	15/30/50V	205ACV 301	
3 Ranges	30/50/100V	205ACV 302	
	50uA	205DCA 100	
DC Ammeter (Moving Coil Type) Accuracy : ±2.0% F.S.	1 Range	100uA	205DCA 101
		500uA	205DCA 102
		3mA	205DCA 103
		10mA	205DCA 104
		100mA	205DCA 105
		200mA	205DCA 106
		300mA	205DCA 107
		500mA	205DCA 108
		500uA	205DCA 109
		1A	205DCA 110
		2.5A	205DCA 111
		3A	205DCA 112
		5A	205DCA 113
		10A	205DCA 114
	2 Ranges	1/10mA	205DCA 200
1/5A		205DCA 201	
1/10A		205DCA 202	
50/500mA		205DCA 203	
3 Ranges	50mA/500mA/5A	205DCA 301	
	100mA/1A/5A	205DCA 302	
	1/5/10A	205DCA 303	

Name	Range	No.	
DC Voltmeter (Moving Coil Type) Accuracy : ±2.0% F.S.	1 Range	1mV	205DCV 100
		1V	205DCV 101
		3V	205DCV 102
		5V	205DCV 103
		6V	205DCV 104
		10V	205DCV 105
		15V	205DCV 106
	2 Ranges	20V	205DCV 107
		50/500mV	205DCV 200
		50/500uA	205DCV 201
		1/10V	205DCV 202
		1/5V	205DCV 203
		2/20V	205DCV 204
		3/15V	205DCV 205
		5/10V	205DCV 206
		5/15V	205DCV 207
		10/50V	205DCV 208
3 Ranges	30/60V	205DCV 209	
	50/500/5000uA	205DCV 301	
	100uA/500uA/1mA	205DCV 302	
	3/10/15V	205DCV 303	
	3/15/300V	205DCV 304	
	3/15/30V	205DCV 305	
DC (Galvanometer Type) Accuracy : ±2.0% F.S.	1 Range	3/30/300V	205DCV 306
		+/- 0.1mA	205G 100
		+/- 0.5mA	205G 101
		+/- 10V	205G 102
		+/- 1A	205G 103
		+/- 3.5G	205G 104
		+/- 3.5mA	205G 105
		+/- 30G	205G 106
		+/- 30mA	205G 107
		+/- 35G	205G 109
		+/- 35mV	205G 110
		+/- 50G	205G 111
+/- 60uA	205G 112		
Custom Accuracy : ±2.0% F.S.	1 Range	+1A-0-5A	205DC 101
		+20uA-0-100uA	205DC 102
		+20mA-0-100mA	205DC 103
		+5V-0-15V	205DC 104
		+50mA/500mA/5A	205DC 105
+3/15/300V	205DC 106		

<http://www.51082245.com/sew.htm> Special Ranges Are Available Upon Request