

## 數位鉤表

### DIGITAL CLAMP METER



**ST-3600**



**ST-3602**



**ST-3620**

- 液晶顯示器3½位，最大讀值1999。
- 過載顯示為"1"。
- 電源不足顯示"B"。
- 反應時間：每次約1秒。
- 讀值鎖定。

電氣規格(23±5°C ≤ 85%RH)

**ST-3600**

**ST-3602**

**ST-3620**

交流電流 (AC A)	200/1500 ±(2.0%讀值+4 位數) (40-1KHz)	200/1500 ±(2.0%讀值+4 位數) (40-1KHz)	200/1500 ±(2.0%讀值+4 位數) (40-1KHz)
交流電壓 (AC V)	200/750 ±(1.5%讀值+2 位數) (40-1KHz)	200/750 ±(1.5%讀值+2 位數) (40-1KHz)	200/750 ±(1.5%讀值+2 位數) (40-1KHz)
直流電流 (DC A)	200/1500 ±(2.0%讀值+4 位數)	200/1500 ±(2.0%讀值+4 位數)	—————
直流電壓 (DC V)	20/200/1000 ±(1.0%讀值+2 位數)	20/1000 ±(1.0%讀值+2 位數)	—————
歐姆 (Ω)	200/1500 ±(1.5%讀值+2 位數)	200/1500 ±(1.5%讀值+2 位數)	200 ±(1.5%讀值+2 位數)
二極體檢查 (Diode)	0-1500mV ±(1.5%讀值+2 位數)	0-1500mV ±(1.5%讀值+2 位數)	—————
蜂鳴器響應	—————	< 100 Ω	< 30 Ω
峰值鎖定	—————	—————	V
鉤部最大內徑	55 公厘		
使用電池	9V (6F 22)*1(顆)		
外形尺寸	245(長)*70(寬)*42(高)公厘		
重量	約 480 克		
使用環境	-10°C~50°C      85%最大相對濕度		
附件	測試線*1(組) 說明書*1(本) 軟袋*1(個) 電池		

## CLAMP METER



**ST-3600**



**ST-3602**



**ST-3620**

### FEATURES

- Display 3½ digit, liquid crystal display with maximum reading of 1999.
- Over range indication : "1" is displayed on highest digit.
- Low battery indication : "B" sign appears on the display.
- Response time : approx.1 second.
- Data hold : for all ranges.

### SPECIFICATIONS

Model	ST-3600	ST-3602 (Auto-Ranges)	ST-3620
ACA	200/1500 ±(2%rdg+4dgt) (40Hz-1KHz)	200/1500 ±(2%rdg+4dgt) (40Hz-1KHz)	200/1500 ±(2%rdg+4dgt) (40Hz-1KHz)
ACV	200/750 ±(1.5%rdg+2dgt) (40Hz-1KHz)	200/750 ±(1.5%rdg+2dgt) (40Hz-1KHz)	200/750 ±(1.5%rdg+2dgt) (40Hz-1KHz)
DCA	200/1500 ±(2%rdg+4dgt)	200/1500 ±(2%rdg+4dgt)	_____
DCV	20/200/1000 ±(1%rdg+2dgt)	200/1000 ±(1%rdg+2dgt)	_____
Ω	200/1500 ±(1.5%rdg+2dgt)	200/1500 ±(1.5%rdg+2dgt)	200 ±(1.5%rdg+2dgt)
Diode check	0-1500mV ±(1.5%rdg+2dgt)	0-1500mV ±(1.5%rdg+2dgt)	_____
Buzzer	_____	Resistance is less then 100Ω	Resistance is less then 30Ω
Peak Hold	_____	_____	V
Conductor Size	ø55mm Max.	ø55mm Max.	ø55mm Max.
Dimensions	245(L) x 70(W) x 41.7(D)mm	245(L) x 70(W) x 41.7(D)mm	245(L) x 70(W) x 41.7(D)mm
Power Source	9V(6F22) x 1	9V(6F22) x 1	9V(6F22) x 1
Weight (Battery Included)	480g Approx.	480g Approx.	480g Approx.
Operating Temperature	-10°C~50°C	-10°C~50°C	-10°C~50°C
Humidity	85%	85%	85%
Current Consumption	10mA Approx.	10mA Approx.	10mA Approx.
Accessories	Test leads (TEL-AL11-1) Carrying case Instruction manual Battery	Test leads (TEL-AL11-1) Carrying case Instruction manual Battery	Test leads (TEL-AL11-1) Carrying case Instruction manual Battery